

# D-400V

## INDIVIDUAL INCOME PAYMENT VOUCHER (FORM REVISION 9-16-08/ INSTRUCTIONS 10-18-22)

### CHANGES FOR THE YEAR

- Only the instructions of Form D-400V was updated for 2022.
- A QR code has been added to the instructions.
- Form D-400V should include the following URL information in the QR code:  
<https://electronic-services.dor.nc.gov/wps/portal/d400v>
- If your company reproduced Form D-400V last year, your data placement for the form should match the approved trained version.
- If your company has not reproduced Form D-400V, then match the SD version.

#### Production Details:

<b>Approved By Date:</b>	December 21, 2022
<b>Form Period Date Effective:</b>	Calendar Year December 31, 2022
<b>For Filing Periods</b>	December 2022 and later
<b>Form Placed in Software:</b>	After December 31, 2022
<b>Unchanged/Updated:</b>	Updated

### 9-12 TEST SAMPLES REQUIRED:

- 1 Blank
- 1 Full Field
- 7 by PDF or 10 by Mail which must include the following:
  - 1 Foreign
  - 6 Or more other Individual and Joint Examples

**Note:** If you do not support one of the required types, list as a limitation.

### BARCODE:

The barcode must read 72701XX006. Replace (XX) with your two-digit Software Developer Identification Number.

Align barcode between Row 61, Column 41-66 and Row 63, Column 41-66. Print the number above the barcode.

### USE:

- 12 point Courier font in scanline
- 12 point Courier font for variable fields
- All capital letters for variable text
- Amount due with 0.00 format
- Correct barcode length
- Correct check digits
- Correct matching line geometry
- Data placement from approved trained version
- Foreign zip code of 00000
- Function Code (06408)
- High resolution bitmap for barcode
- Matching alignment between the full field and test samples
- No punctuation or special characters in address field
- Period Ending Chart
- Right aligned amount due
- Scanline period 20222
- Various ID numbers using the prefixes of 999, 900, 000 or 666 for FEINs/SSNs

## BARCODE DIMENSIONS:

- BARCODE LENGTH MUST MEASURE MORE THAN 2 5/8" BUT LESS THAN 2 3/4" FOR NEW SOFTWARE PROVIDERS
- MAKE SURE THE BARCODE READS AND IS PROPERLY PLACED BASED ON THE SPECIFICATIONS GIVEN
- SYMBOLOGY CODE 39
- DENSITY 4.18 CPI
- HEIGHT 0.500
- HIGH RESOLUTION BITMAP FOR BARCODES
- RATIO 3:1

## TEST SAMPLES:

- CONFIRM DATA/TEXT PLACEMENT MATCHES THE SD TEMPLATE
- PLEASE NOTE: BLANK AND FULL FIELD ARE REQUIRED BUT ARE NOT CONSIDERED TEST SAMPLES
- IF SENDING IN BY EXPRESS MAIL, PLEASE SEND ADDITIONAL TEST SAMPLES AS REQUIRED
- INCLUDE ONE TEST SAMPLE EXCEEDING \$999.00
- INCLUDE ONE TEST SAMPLE WITH PRIMARY AND SPOUSE
- INCLUDE ONE TEST SAMPLE WITH PRIMARY MIDDLE INITIAL
- INCLUDE ONE TEST SAMPLE WITH SPOUSE MIDDLE INITIAL
- USE THE FIELD DESCRIPTION FORMATTING FOR PLACEMENT OF VARIABLE DATA
- USE A DIFFERENT AMOUNT FOR EACH FIELD
- ENSURE EACH LINE IS POPULATED ACROSS REQUIRED TEST SAMPLES

PROPOSED VARIETY OF D-400V TEST SAMPLES							
TEST SAMPLE:	1	2	3	4	5	6	7
TAX TYPE	IND	IND	IND	IND	IND	IND	IND
CY/FY	2022	2022	2022	2022	2022	2022	2022
FOREIGN	N	N	Y	N	N	N	N

**Placement of Variable Data**

Line Number	Identification	Print Position	Field Length	Print Position	Field Description
50	T/P SSN	7	9	15	Numeric; No dashes Print number consecutively.
50	T/P Last Name	23	4	26	Alpha; First four characters of last name.
50	Address	31	4	34	Alphanumeric; First four characters of address.
50	Zip Code	39	5	43	Numeric; 5-digit zip code <b>If Foreign address, enter 5 zeroes as this is a data captured field.</b>
50	Spouse SSN	52	9	60	Numeric; No dashes Print number consecutively
52	T/P First Name	7	14	20	Alpha
52	T/P Middle Initial	22	1	22	Alpha
52	T/P Last Name	24	19	42	Alpha
52	Spouse First Name	45	14	58	Alpha
52	Spouse Middle Initial	60	1	60	Alpha
52	Spouse Last Name	62	19	80	Alpha
54	Address	7	35	41	Alphanumeric
54	Calendar Year	55	4	58	XXXX, Numeric
56	City	7	20	26	Alpha
56	State	30	2	31	Alpha
56	Zip Code	35	5	39	Numeric; 5-digit zip code <b>If Foreign address, enter 5 zeroes.</b>
56	Foreign Country	49	10	58	Alpha; if applicable
58	Amount Due	67	11	77	Numeric; With 0.00